



**solavanti** lighting



**PERFORMANCE**<sup>10</sup>

**LTS**<sup>®</sup>  
LIGHT & LUMINAIRES



## Salto



Salto I 110



NEW

Salto I LED 110



Salto II 111



Salto III 111



Salto IV 111

## Filou



Filou I 112



NEW

Filou I LED 112



Filou II 112

## Elvis



Elvis 113

## Clipo



Clipo 113



NEW

Clipo LED 113

## Roy



Roy I 114



Roy II 114

## Amigo



Amigo 115

## Impla



Impla I 115

## Kobra



Kobra 115

## Monopoint



Monopoint 117

## Fastenings



Fastenings 117

Available in various shapes and designs for ambient illumination. Rod-mounted luminaires are particularly suited for accent illumination.


# Rod-mounted Spotlights



## Salto I | QR-CBC51 | max. 50 W

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90°
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ colour: alu

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------




LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	⚡
☞ QR-CBC51 / GU5.3	max. 50 W	NSP 5001 NSP 5002 NSP 5003 NSP 5005 NSP 5006 NSP 5007 NSP 5008	NSP 5031 NSP 5032 NSP 5033 NSP 5035 NSP 5036 NSP 5037 NSP 5038	Fastening 1 Fastening 2 Fastening 3 Fastening 5 Fastening 6 Fastening 7 Fastening 8	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. TRE70 Electronic transf. - Transformer integral TRE70 Electronic transf.

## Salto I | LED | 3 W

- fi high-power LED with high-grade aluminium reflector
- fi PRI reflector technique for glare-free light and maximum luminous efficiency
- fi light head pivots through 90°
- fi housing and pendant rod made from anodised aluminium
- fi converter to be ordered separately
- fi Other LED colours available on request.
- fi Only suitable for permanently accessible ceiling systems!
- fi colour: alu

120-240V 60Hz	IP20	CE
------------------	------	----




LM	Wattage	⚡	🇩🇪	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117
☞ 1 x LED cw	1 x 3 W	6°	6500 K	NSPLED 010302. 01 NSPLED 010302. 08	NSPLED 010302. 31 NSPLED 010302. 38	Fastening 1 Fastening 8
		35°	6500 K	NSPLED 010322. 01 NSPLED 010322. 08	NSPLED 010322. 31 NSPLED 010322. 38	Fastening 1 Fastening 8
Accessories	Converter (1 luminaire) Converter (7 luminaires)			CVLED 60 CVLED 420		



**Salto II | QR-CBC 51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page 700
---------------------	------	----	----------

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90°
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color: alu




LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	⚡
----	---------	------------------	-------------------	-----------------	---

QR-CBC 51 / GU5.3 max.50 W	NSP 5201	NSP 5231	Fastening 1	TRE70 Electronic transf.
	NSP 5202	NSP 5232	Fastening 2	Transformer integral
	NSP 5203	NSP 5233	Fastening 3	TRE70 Electronic transf.
	NSP 5205	NSP 5235	Fastening 5	TRE70 Electronic transf.
	NSP 5206	NSP 5236	Fastening 6	-
	NSP 5207	NSP 5237	Fastening 7	Transformer integral
	NSP 5208	NSP 5238	Fastening 8	TRE70 Electronic transf.

**Salto III | QR-CBC 51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page 700
---------------------	------	----	----------

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90°
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color: alu




LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p. 117	⚡
----	---------	------------------	-------------------	------------------	---

QR-CBC 51 / GU5.3 max.50 W	NSP 5301	NSP 5331	Fastening 1	TRE70 Electronic transf.
	NSP 5302 <td>NSP 5332 <td>Fastening 2 <td>Transformer integral</td> </td></td>	NSP 5332 <td>Fastening 2 <td>Transformer integral</td> </td>	Fastening 2 <td>Transformer integral</td>	Transformer integral
	NSP 5303 <td>NSP 5333 <td>Fastening 3 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5333 <td>Fastening 3 <td>TRE70 Electronic transf.</td> </td>	Fastening 3 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.
	NSP 5305 <td>NSP 5335 <td>Fastening 5 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5335 <td>Fastening 5 <td>TRE70 Electronic transf.</td> </td>	Fastening 5 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.
	NSP 5306 <td>NSP 5336 <td>Fastening 6 <td>-</td> </td></td>	NSP 5336 <td>Fastening 6 <td>-</td> </td>	Fastening 6 <td>-</td>	-
	NSP 5307 <td>NSP 5337 <td>Fastening 7 <td>Transformer integral</td> </td></td>	NSP 5337 <td>Fastening 7 <td>Transformer integral</td> </td>	Fastening 7 <td>Transformer integral</td>	Transformer integral
	NSP 5308 <td>NSP 5338 <td>Fastening 8 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5338 <td>Fastening 8 <td>TRE70 Electronic transf.</td> </td>	Fastening 8 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.

**Salto IV | QR-CBC 51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page 700
---------------------	------	----	----------


- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90°
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color: alu



LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	⚡
----	---------	------------------	-------------------	-----------------	---

QR-CBC 51 / GU5.3 max.50 W	NSP 5401	NSP 5431	Fastening 1	TRE70 Electronic transf.
	NSP 5402 <td>NSP 5432 <td>Fastening 2 <td>Transformer integral</td> </td></td>	NSP 5432 <td>Fastening 2 <td>Transformer integral</td> </td>	Fastening 2 <td>Transformer integral</td>	Transformer integral
	NSP 5403 <td>NSP 5433 <td>Fastening 3 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5433 <td>Fastening 3 <td>TRE70 Electronic transf.</td> </td>	Fastening 3 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.
	NSP 5405 <td>NSP 5435 <td>Fastening 5 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5435 <td>Fastening 5 <td>TRE70 Electronic transf.</td> </td>	Fastening 5 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.
	NSP 5406 <td>NSP 5436 <td>Fastening 6 <td>-</td> </td></td>	NSP 5436 <td>Fastening 6 <td>-</td> </td>	Fastening 6 <td>-</td>	-
	NSP 5407 <td>NSP 5437 <td>Fastening 7 <td>Transformer integral</td> </td></td>	NSP 5437 <td>Fastening 7 <td>Transformer integral</td> </td>	Fastening 7 <td>Transformer integral</td>	Transformer integral
	NSP 5408 <td>NSP 5438 <td>Fastening 8 <td>TRE70 Electronic transf.</td> </td></td>	NSP 5438 <td>Fastening 8 <td>TRE70 Electronic transf.</td> </td>	Fastening 8 <td>TRE70 Electronic transf.</td>	TRE70 Electronic transf.

Fastenings  
For details see  
page 117





**Filou I | QR-CBC 51 | max. 50 W**


120V  
12V  
60Hz

IP20

CE

Page700

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90° via adjusting stick
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color combination luminaire body/screen: alu/black, alu/alu, black/alu, RAL/RAL



LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p. 117	
☞ QR-CBC51 / GU5.3	max. 50 W	NFP 5001 NFP 5002 NFP 5003 NFP 5005 NFP 5006 NFP 5007 NFP 5008	NFP 5031 NFP 5032 NFP 5033 NFP 5035 NFP 5036 NFP 5037 NFP 5038	Fastening 1 Fastening 2 Fastening 3 Fastening 5 Fastening 6 Fastening 7 Fastening 8	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. TRE70 Electronic transf. - Transformer integral TRE70 Electronic transf.


**Filou I | LED | 3W**

120-240V  
60Hz

IP20

CE

- ☑ high-power LED with high-grade aluminium reflector
- ☑ flPRI reflector technique for glare-free light and maximum luminous efficiency
- ☑ light head pivots through 90° via adjusting stick
- ☑ housing and pendant rod made from anodised aluminium
- ☑ converter to be ordered separately
- ☑ Other LED colours available on request!
- ☑ Only suitable for permanently accessible ceiling systems!
- ☑ color combination luminaire body/screen: alu/black, alu/alu, black/alu, RAL/RAL



LM	Wattage	Beam angle	Color	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117
☞ 1 x LED cw	1 x 3 W	6°	6500 K	NFPLED 010302.01 NFPLED 010302.08	NFPLED 010302.31 NFPLED 010302.38	Fastening 1 Fastening 8
		35°	6500 K	NFPLED 010322.01 NFPLED 010322.08	NFPLED 010322.31 NFPLED 010322.38	Fastening 1 Fastening 8
Accessories Converter	(1 luminaire)			CVLED60		
Converter	(7 luminaires)			CVLED420		

**Filou II | QR-CBC51 | max. 50 W**


120V  
12V  
60Hz

IP20

CE

Page700

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivots through 90° via adjusting stick
- ☑ easy relamping
- ☑ housing and pendant rod made from anodised aluminium
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color combination luminaire body/decorative ring: alu/black, alu/alu, black/alu, RAL/RAL




LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	
☞ QR-CBC 51 / GU5.3	max. 50 W	NFP 5201 NFP 5202 NFP 5203 NFP 5205 NFP 5206 NFP 5207 NFP 5208	NFP 5231 NFP 5232 NFP 5233 NFP 5235 NFP 5236 NFP 5237 NFP 5238	Fastening 1 Fastening 2 Fastening 3 Fastening 5 Fastening 6 Fastening 7 Fastening 8	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. TRE70 Electronic transf. - Transformer integral TRE70 Electronic transf.



**Elvis | QR-CBC51 | max. 50 W**

- rod-mounted spotlight available with different pendant lengths and wall fastenings
- light head pivotable with handle bar
- easy relamping
- housing and pendant rod made from high-grade aluminium profile, pendant rod made from metal
- transformer to be ordered separately, if necessary
- use IRC lamps only up to 35 W
- protection class III applies only in combination with suitable transformer
- color: chrome matt, white

120V 12V 60Hz IP20 CE Page700



Decorative glass ring

LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	
----	---------	------------------	-------------------	-----------------	--


QR-CBC51 / GU5.3 max. 50 W	NEP 5401	NEP 5431	Fastening 1	TRE70 Electronic transf.
	NEP 5402	NEP 5432	Fastening 2	Transformer integral
	NEP 5405	NEP 5435	Fastening 5	TRE70 Electronic transf.
	NEP 5406	NEP 5436	Fastening 6	-
	NEP 5407	NEP 5437	Fastening 7	Transformer integral
	NEP 5408	NEP 5438	Fastening 8	TRE70 Electronic transf.

Accessories Decorative glass ring: clear blue NEP 90 green NEP 91 matt NEP 92 NEP 93

**Clipo | QR-CBC 51 | max. 50 W**

- rod-mounted spotlight available with different wall fastenings
- light head pivots through 90°
- easy relamping
- housing and pendant rod made from anodised aluminium (chrome matt), luminaire holder made from heat-resistant polycarbonate (black)
- transformer to be ordered separately, if necessary
- use IRC lamps only up to 35 W
- protection class III applies only in combination with suitable transformer

120V 12V 60Hz IP20 CE Page700




LM	Wattage	Pendant rod 7.8"	Fastening p.117	
----	---------	------------------	-----------------	--

QR-CBC51 / GU5.3 max. 50 W	NAA 5241	Fastening 1	TRE70 Electronic transf.
	NAA 5242	Fastening 2	Transformer integral
	NAA 5246	Fastening 6	-
	NAA 5247	Fastening 7	Transformer integral
	NAA 5248	Fastening 8	TRE70 Electronic transf.

**Clipo | LED | 3 W**

- high-power LED with high-grade aluminium reflector
- PRI reflector technique for glare-free light and maximum luminous efficiency
- light head pivots through 90°
- housing and pendant rod made from anodised aluminium (chrome matt), luminaire holder made from heat-resistant polycarbonate (black)
- converter to be ordered separately
- Other LED colours available on request.
- Only suitable for permanently accessible ceiling systems.

120-240V 60Hz IP20 CE




LM	Wattage		Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117
----	---------	--	------------------	-------------------	-----------------

1 x LED cw	1 x 3 W	6°	6500 K	NAALED010302.01	NAALED010302.31	Fastening 1
				NAALED010302.08	NAALED010302.38	Fastening 8
	35°	6500 K	NAALED010322.01	NAALED010322.31	Fastening 1	
			NAALED010322.08	NAALED010322.38	Fastening 8	

Accessories Converter (1 luminaire) CVLED60 Converter (7 luminaires) CVLED420

Fastenings For details see page 117






**Roy I | QR-CBC 51 | max. 50 W**

- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivotable via tilting and swivel joint
- ☑ easy relamping
- ☑ housing and pendant rod made from high-grade aluminium, pendant rod made from metal
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color: chrome matt

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------




LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p.117	
☎ QR-CBC 51 / GU5.3	max. 50 W	NRP 5001 NRP 5002 NRP 5005 NRP 5006 NRP 5007 NRP 5008	NRP 5031 NRP 5032 NRP 5035 NRP 5036 NRP 5037 NRP 5038	Fastening 1 Fastening 2 Fastening 5 Fastening 6 Fastening 7 Fastening 8	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. - Transformer integral TRE70 Electronic transf.



**Roy III | QR-CBC 51 | 2 x max. 50 W**


- ☑ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☑ light head pivotable via tilting and swivel joint
- ☑ easy relamping
- ☑ housing and pendant rod made from high-grade aluminium, pendant rod made from metal
- ☑ transformer to be ordered separately, if necessary
- ☑ use IRC lamps only up to 35 W
- ☑ protection class III applies only in combination with suitable transformer
- ☑ color: chrome matt

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------



LM	Wattage	Pendant rod 3.9"	Pendant rod 11.8"	Fastening p. 117	
☎ QR-CBC 51 / GU5.3	2 x max. 50 W	NRP 5201 NRP 5206 NRP 5208	NRP 5231 NRP 5236 NRP 5238	Fastening 1 Fastening 6 Fastening 8	TRE105 Electronic transf. - TRE105 Electronic transf.

Fastenings  
For details see  
page 117






**Amigo | QR-CBC51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------

- ☒ rod-mounted spotlight available with different pendant lengths and wall fastenings
- ☒ light head pivotable via tilting and swivel joint
- ☒ easy relamping
- ☒ housing made from brass, pendant rod made from metal
- ☒ transformer to be ordered separately, if necessary
- ☒ use IRC lamps only up to 35 W
- ☒ protection class III applies only in combination with suitable transformer
- ☒ color: chrome matt




LM	Wattage	Pendant rod 3.9"	Fastening p.117	
☒ QR-CBC51 / GU5.3	max. 50 W	NAP 5001 NAP 5002 NAP 5005 NAP 5006	Fastening 1 Fastening 2 Fastening 5 Fastening 6	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. -

**Implal | QR-CBC51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------

- ☒ rod-mounted spotlight available with different wall fastenings
- ☒ light head pivotable
- ☒ easy relamping
- ☒ housing and pendant rod made from anodised aluminium
- ☒ transformer to be ordered separately, if necessary
- ☒ use IRC lamps only up to 35 W
- ☒ protection class III applies only in combination with suitable transformer
- ☒ color: alu




LM	Wattage	Pendant rod 3.9"	Fastening p.117	
☒ QR-CBC51 / GU5.3	max. 50 W	NIM 5101 NIM 5102 NIM 5105 NIM 5106	Fastening 1 Fastening 2 Fastening 5 Fastening 6	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. -

**Kobra | QR-CBC51 | max. 50 W**

120V 12V 60Hz	IP20	CE	Page700
---------------------	------	----	---------

- ☒ rod-mounted spotlight available with different wall fastenings
- ☒ light head rotatable and pivotable via lever arm
- ☒ easy relamping
- ☒ housing made from brass, lever arm made from stainless steel
- ☒ transformer to be ordered separately, if necessary
- ☒ use IRC lamps only up to 35 W
- ☒ protection class III applies only in combination with suitable transformer
- ☒ color: chrome



LM	Wattage	Lever arm 19.7"	Fastening p.117	
☒ QR-CBC 51 / GU5.3	max. 50 W	NKP 5051 NKP 5052 NKP 5055 NKP 5056	Fastening 1 Fastening 2 Fastening 5 Fastening 6	TRE70 Electronic transf. Transformer integral TRE70 Electronic transf. -



Business Campus, Garching



Nycomed, Konstanz

## Monopoint




### Low-voltage contact plug

12 V / max. 6 A  
for rod-mounted luminaires and pendant luminaires  
rotates through 360° in contact socket  
suitable for contact sockets LA 40 B and LA 40 BA  
color: black, white  
for pendant rod: M 6 x1: **LA 40 S**  
M 8 x1: **LA 41 S**  
M 10 x1: **LA 42 S**



### Recessed contact socket

12 V / max. 6 A  
color: black, white




**LA 40 B**




### Recessed contact socket with compensating cover

12 V / max. 100 W  
when closed ceiling system  
the transformer can be recessed  
color: black, white




**LA 40 BA**



### Low-voltage recessed ceiling rose

for mineral fibrous material or  
plasterboard suitable for  
recessed contact socket LA 40 B  
fixing base included  
color: black, white




**LA 40 R**



### Flush-mounted box


flame-resistant  
for 1.4" diameter  
for the installation of  
low-voltage recessed  
ceiling rose LA 40 R



**LA 40 D**

## Fastenings

for rod-mounted spotlights



### Fastening 1

any individual fastening for rod-mounted  
luminaires with thread



### Fastening 2

low-voltage luminaires, which  
are equipped with the electronic adapter  
LA30 can be connected to 120V contact  
tracks; dimmable from 20–50 VA  
suitable for Erco, Staff, Hoffmeister, Nokia,  
iGuzzini, Eutrac, etc.  
color: black, white  
**LA 30 ED**



### Fastening 3

ceiling rose for individual installation  
color: black, white, gold, chrome,  
chrome matt

**L2 KL**




### Fastening 5

low-voltage contact plug for  
low-voltage Monopoint  
suitable for low-voltage outlet Euroline  
(s. Page 496)  
color: black, white



### Fastening 6

for low-voltage contact track Eutrac  
(s. page 694)  
color: black, white



### Fastening 7

Monopoint surface-mounted with  
transformer 50 VA  
without rod  
color: silver, black, white

**LA 50**



### Fastening 8

ceiling socket with fixing clasp for  
continuous height adjustment  
color: alu



# solavanti lighting



SOLAVANTI LIGHTING, LLC

Dallas, Texas

Tel.: 1.866.356.4458

Fax: 1.866.516.1924

[www.solavantilighting.com](http://www.solavantilighting.com)